



ECOJET 70.20 ST

ECO-IDROPULTRICE AD ACQUA CALDA

HOT WATER ECO-WASHER

DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	400 V / ~3 / 50 Hz / 32 A		
	440 V / ~3 / 60 Hz / 29 A		
Potenza totale installata: Power output:	22,2 kW		
Potenza motore: Power output motor:	3,0 kW		
Potenza riscaldamento: Boiler group power:	20 kW		
Portata d'acqua: Water flow rate:	4,0 l/min	5,5 l/min	7,0 l/min
Temperatura di esercizio (partendo da acqua a 15 °C): Operating temperature (starting with water at 15 °C):	89 °C	64 °C	57 °C
Pressione acqua (max): Water pressure (max):	150 bar		
Caldia + termoriscaldatori: Boiler + heating elements:	AISI 304 + INCOLOY 800		
Temperatura di entrata acqua (max): Inlet water temperature (max):	35 °C		
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	90 °C		
Volume serbatoio interno (se previsto): Internal reserve tank volume (if provided):	-		
Livello acustico: Acoustic level:	49 dB @ 1 m		
	41 dB @ 5 m		
Struttura e pannelli: Body and panels:	AISI 304		
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	5 m		
	78 x 40 x 63 cm		
	62 kg		

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con attacchi rapidi
Spray gun with quick conn.



Lancia con attacchi rapidi
Lance with quick conn.



Ugello
Nozzle

15015 2502 25025
4,0 l/min 5,5 l/min 7,0 l/min

