

IDROELETRIKA

ECOcube 100.00 CW

ECO-IDROPULITRICE AD ACQUA FREDDA
con SERBATOIO INTERNO
COLD WATER ECOLOGIC PRESSURE WASHER
with INTERNAL WATER TANK



DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	230 V / ~1 / 50-60 Hz / ≈13 A 400 V / ~3 / 50-60 Hz / ≈7 A
Potenza totale installata: Power output:	3,0 kW
Potenza motore: Power output motor:	3,0 kW
Potenza riscaldamento: Boiler group power:	NO
Portata d'acqua: Water flow rate:	6,9 l/min 8,3 l/min 9,8 l/min
Temperatura di esercizio (max): Operating temperature (max):	35 °C (80 °C a richiesta on request)
Pressione acqua (max): Water pressure (max):	70 ÷ 150 bar regolabile adjustable
Caldaia + termoriscaldatori: Boiler + heating elements:	NO
Temperatura di entrata acqua (max): Inlet water temperature (max):	35 °C (80 °C a richiesta on request)
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	NO
Serbatoio interno acqua: Internal reserve tank:	44 l
Livello acustico: Acoustic level:	49 dB @ 1 m 41 dB @ 5 m
Struttura e pannelli: Body and panels:	AISI 304
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	5 m 61 x 95 x 80 cm 50 kg

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con raccordi rapidi
Spray gun with quick connect.



Lancia con raccordi rapidi
Lance with quick connect.



Ugello
Nozzle

