

# IDROELETRIKA

## ECOcube 150.00 CW

ECO-IDROPULITRICE AD ACQUA FREDDA  
con SERBATOIO INTERNO

COLD WATER ECOLOGIC PRESSURE WASHER  
with INTERNAL WATER TANK



### DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	230 V / ~1 / 50-60 Hz / ≈18 A	400 V / ~3 / 50-60 Hz / ≈11 A	
Potenza totale installata: Power output:	4,0 kW		
Potenza motore: Power output motor:	4,0 kW		
Potenza riscaldamento: Boiler group power:	NO		
Portata d'acqua: Water flow rate:	11,1 l/min	12,6 l/min	14,0 l/min
Temperatura di esercizio (max): Operating temperature (max):	35 °C (80 °C a richiesta   on request)		
Pressione acqua (max): Water pressure (max):	150 bar		
Caldaia + termoriscaldatori: Boiler + heating elements:	NO		
Temperatura di entrata acqua (max): Inlet water temperature (max):	35 °C (80 °C a richiesta   on request)		
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	NO		
Serbatoio interno acqua: Internal reserve tank:	44 l or 88 l		
Livello acustico: Acoustic level:	49 dB @ 1 m 41 dB @ 5 m		
Struttura e pannelli: Body and panels:	AISI 304		
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	5 m 75 x 95 x 80 cm 60 kg		

### KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione  
High pressure hose



Pistola con raccordi rapidi  
Spray gun with quick connect.



Lancia con raccordi rapidi  
Lance with quick connect.



Ugello  
Nozzle

