

ECOjet 100.00 CW

ECO-IDROPULITRICE AD ACQUA FREDDA
COLD WATER ECOLOGIC PRESSURE WASHER



DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	230 V / ~1 / 50-60 Hz / ≈13 A 400 V / ~3 / 50-60 Hz / ≈7 A	
Potenza totale installata: Power output:	3,0 kW	
Potenza motore: Power output motor:	3,0 kW	
Potenza riscaldamento: Boiler group power:	NO	
Portata d'acqua: Water flow rate:	8,3 l/min	9,8 l/min
Temperatura di esercizio (max): Operating temperature (max):	35 °C	
Pressione acqua (max): Water pressure (max):	150 bar	
Caldia + termoriscaldatori: Boiler + heating elements:	NO	
Temperatura di entrata acqua (max): Inlet water temperature (max):	35 °C	
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	NO	
Serbatoio interno acqua: Internal reserve tank:	NO	
Livello acustico: Acoustic level:	49 dB @ 1 m 41 dB @ 5 m	
Struttura e pannelli: Body and panels:	AISI 304	
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	5 m 50 x 40 x 36 cm 45 kg	

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con raccordi rapidi
Spray gun with quick connect.



Lancia con raccordi rapidi
Lance with quick connect.



Ugello
Nozzle

