



ECOjet 40.00 CW

ECO-IDROPULITRICE AD ACQUA FREDDA
COLD WATER ECOLOGIC PRESSURE WASHER

DATI TECNICI | TECHNICAL DATA

| | | |
|---|------------------------------|------------------------------|
| Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request): | 230 V / ~1 / 50-60 Hz / ≈7 A | 400 V / ~3 / 50-60 Hz / ≈4 A |
| Potenza totale installata: Power output: | 1,5 kW | |
| Potenza motore: Power output motor: | 1,5 kW | |
| Potenza riscaldamento: Boiler group power: | NO | |
| Portata d'acqua: Water flow rate: | 2,8 l/min | 4,0 l/min |
| Temperatura di esercizio (max): Operating temperature (max): | 35 °C | |
| Pressione acqua (max): Water pressure (max): | 150 bar | |
| Caldaia + termoriscaldatori: Boiler + heating elements: | NO | |
| Temperatura di entrata acqua (max): Inlet water temperature (max): | 35 °C | |
| Termostato di sicurezza su caldaia: Safety thermostat on boiler: | NO | |
| Serbatoio interno acqua: Internal reserve tank: | NO | |
| Livello acustico: Acoustic level: | 49 dB @ 1 m | 41 dB @ 5 m |
| Struttura e pannelli: Body and panels: | AISI 304 | |
| Lunghezza cavo, misure e peso: Power cord length, dimensions and weight: | 5 m | 50 x 40 x 36 cm 30 kg |

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con raccordi rapidi
Spray gun with quick connect.



Lancia con raccordi rapidi
Lance with quick connect.



Ugello
Nozzle

