

ECOpower 150.40 ST

ECO-IDROPULITRICE con PRE-RISCALDAMENTO ACQUA
ECOLOGIC HIGH PRESSURE WASHER with PRE-HEATING



DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	400-415-440-480 V / ~3 / 50-60 Hz / ≈63 A		
Potenza totale installata: Power output:	44,0 kW		
Potenza motore: Power output motor:	4,0 kW		
Potenza riscaldamento: Boiler group power:	40,0 kW		
Portata d'acqua: Water flow rate:	11,1 l/min	12,6 l/min	14,0 l/min
Temperatura max. di esercizio (incremento): Max. operating temperature (increase):	90 °C (+53 °C)	90 °C (+47 °C)	90 °C (+42 °C)
Pressione acqua (max): Water pressure (max):	150 bar		
Caldiaia + termoriscaldatori: Boiler + heating elements:	AISI 304 + AISI 316L (or INCOLOY 800/825)		
Temperatura di entrata acqua (max): Inlet water temperature (max):	55 °C		
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	90 °C		
Temperatura acqua in serbatoio (max): Water temperature in tank (max):	55 °C		
Serbatoio interno per pre-riscaldamento acqua: Internal water tank for pre-heating:	176 l		
Livello acustico: Acoustic level:	49 dB @ 1 m 41 dB @ 5 m		
Struttura e pannelli: Body and panels:	AISI 304		
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	4 m 90 x 140 x 95 cm 186 kg		

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con raccordi rapidi
Spray gun with quick connect.



Lancia con raccordi rapidi
Lance with quick connect.



Ugello
Nozzle

