

ECOpower 80.14 ST

ECO-IDROPULITRICE con PRE-RISCALDAMENTO ACQUA
ECOLOGIC HIGH PRESSURE WASHER with PRE-HEATING



DATI TECNICI | TECHNICAL DATA

Alimentazioni principali disponibili (altre a richiesta): Available most common power supplies (others on request):	230 V / ~3 / 60 Hz / ≈44 A 400-415-440-480 V / ~3 / 50-60 Hz / ≈24 A	
Potenza totale installata: Power output:	15,7 kW	
Potenza motore: Power output motor:	2,2 kW	
Potenza riscaldamento: Boiler group power:	13,5 kW	
Portata d'acqua: Water flow rate:	5,5 l/min	6,9 l/min
Temperatura max. di esercizio (incremento): Max. operating temperature (increase):	90 °C (+36 °C)	90 °C (+29 °C)
Pressione acqua (max): Water pressure (max):	150 bar	
Caldia + termoriscaldatori: Boiler + heating elements:	AISI 304 + AISI 316L (or INCOLOY 800/825)	
Temperatura di entrata acqua (max): Inlet water temperature (max):	55 °C	
Termostato di sicurezza su caldaia: Safety thermostat on boiler:	90 °C	
Temperatura acqua in serbatoio (max): Water temperature in tank (max):	55 °C	
Serbatoio interno per pre-riscaldamento acqua: Internal water tank for pre-heating:	44 l	
Livello acustico: Acoustic level:	49 dB @ 1 m 41 dB @ 5 m	
Struttura e pannelli: Body and panels:	AISI 304	
Lunghezza cavo, misure e peso: Power cord length, dimensions and weight:	4 m 61 x 95 x 80 cm 94 kg	

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT

Tubo alta pressione
High pressure hose



Pistola con raccordi rapidi
Spray gun with quick connect.



Lancia con raccordi rapidi
Lance with quick connect.



Ugello
Nozzle

